

FOREST RMS RECESSED MOTORIZED SYSTEM

FOREST RMS Recessed Motorized System FOREST SHUTTLE Motors

WHERE DESIGN BECOMES REALITY



FOREST RECESSED MOTORIZED SYSTEM





Scan for more information on the FOREST RMS Recessed Motorized System

RMS RECESSED MOTORIZED SYSTEM

- Heavy duty aluminum extrusion, white, powder coated and lubricated with a patented process. Ultra-quiet and smooth operation for contract or residential applications.
- Maximum weight is 8 lbs/ft.
- Ultra-quiet, smooth operation with any Forest Shuttle motor. Shuttle motor specs can be found on the pages that follow.
- All Forest motors and tracks come with a 10-year warranty.

ASSEMBLED SYSTEM

Includes track, masters, pinchpleat or ripplefold carriers, recess profile, fixing strip, wedge, motor, pulley, cover plate, power supply, and Diamond Sense remote or Diamond Sense wall switch.

RMS	COMPONENT	RMS	COMPONENT
	52925-25 Shuttle HD (M) 52925-59 Shuttle HD (M) black 52939-25 Shuttle Eco (S) 52923-25 Shuttle L See motor specs on pages that follow		52931-25D white 59D black +10% Diamond Sense Remote RF, 15 channel w/ holder, range 98'
•	52928-25 Power Cord, 7' 6" 52934-25 Power Cord, 16' includes 24 volt power supply		52933-25 white 59 black +10% Diamond Sense Wall Switch 2 channel
•	52926-25 Shuttle iOn I Includes battery pack and charger with cable. See motor specs on pages that follow		52947-25 Wireless Connector () One way transmitter to control drapery by third party app or by home automation. Works with all Forest Shuttle & tubular motors.
•	52949-25 Battery Pack Lithium iOn battery charger for use with Shuttle iOn	- 633	
•	52924-59 Power Cord for use with Shuttle iOn battery charger		52948-25 59 black +10% Wi-Fi Dongle Bi-directional communication using Forest Connect app. Use with Forest Shuttle HD, L & Eco.

Denotes a Forest favorite.


FOREST RECESSED MOTORIZED SYSTEM

RMS RECESSED MOTORIZED SYSTEM CONTINUED

RMS		COMPONENT	RMS		COMPONENT
•		51623-25 RMS Track white 23' x 10 tracks/bundle bundle = 230'	•		Two Piece Connected Snap Carrier w/ Square Base, in plastic sleeve. Use 1 1/4" snap tape 2114-25, 59 black 60% fullness, 2 5/8" OC 2111-25, 65 brown, 90 silver 80% fullness, 2 3/8" OC
•	a to to	3803-25 Track Connector		Ó	2112-25, 59 black 100% fullness, 2 1/8" OC 2115-25, 59 black 120% fullness, 1 7/8" OC
•		51723-25 Recess Profile, 23' Order same length as track	•		9112-25 Transport Belt
•		51724-25 Recess Profile Fixing Strip, 23' Order 6" shorter than track	•		53903-25 Motor Pulley Connects motor to track
•		53914-25 Recess Profile Wedge Order 1 per track	•		53910-25 Return Pulley
•		53908-25 Overlap Right 53909-25 Underlap Left FMS Plus Master Carrier	•		53911-25 Upside Down Pulley
•		52008-25 Slim Line Klick Carrier Draperies hang to conceal track	•		53912-25 Cover Plate for Recess Motor and Return Pulley
•		52009-25 Ball Bearing Carrier for motorization	•		53913-25 Cover Plate for Recess Motor, Upside Down Motor, and Return Pulley

Denotes a Forest favorite.

FOREST SHUTTLE MOTOR SPECIFICATIONS



SHUTTLE® HD (M) SHUTTLE[®] ECO (S) SHUTTLE[®] L



Scan for How To videos on the FOREST YOUTUBE CHANNEL.








VOLTAGE SHUTTLE	24V DC	24V DC	100-240V, 50-60Hz 0.8A
RECEIVER	Internal, optional	Internal	Internal
POWER SUPPLY	External, 100-240V AC - 1.5A, 50-60Hz; Output 24V DC - 2.7A	External, 100-240V AC - 0.8A, 50-60Hz; Output 24V DC - 2.5A	Internal
MAX POWER	65W	40W	40W
TORQUE	1.5 Nm	1.0 Nm	1.0 Nm
TRAVEL SPEED	5.5″ per second standard 7″ per second maximum	5.5" per second standard 7" per second maximum	5.5" per second standard 7" per second maximum
NOISE LEVEL	< 40 dB(A)	< 40 dB(A)	< 40 dB(A)
MAXIMUM WEIGHT	160 lbs per motor 120 lbs per motor - curved track	100 lbs per motor 90 lbs per motor - curved track	100 lbs per motor 90 lbs per motor - curved track
DIMENSIONS	2.76" x 1.97" x 9.5"	2.76" x 1.97" x 7.5"	2.76" x 1.97" x 11"
CERTIFICATIONS/MARKINGS	CE/FCC/DOE	CE/FCC/DOE	CE/FCC/DOE
COLOR OPTIONS	White / Black	White	White
TOUCH CONTROL TECHNOLOGY	\checkmark	\checkmark	\checkmark
INTEGRATED EMERGENCY CONTROL	\checkmark	\checkmark	\checkmark
RF COMMUNICATION STANDARD	\checkmark	\checkmark	\checkmark
Z-WAVE COMMUNICATION	-	-	\checkmark
AUTOMATION SYSTEM COMPATIBLE	$\sqrt{\rm using}$ RS485 & dry contacts	$\sqrt{\rm using}~{ m RS485}$ & dry contacts	$\sqrt{\rm using}$ RS485 & dry contacts
WI-FI COMPATIBLE	\checkmark	\checkmark	\checkmark
WORKS WITH DS-XL LED DIMMER	\checkmark	\checkmark	\checkmark
WORKS WITH WIRELESS CONNECTOR	\checkmark	\checkmark	\checkmark
CAN BE USED WITH CURVED TRACK	\checkmark	\checkmark	\checkmark
PLUG & PLAY	\checkmark	\checkmark	\checkmark
WARRANTY	10 Years	10 Years	10 Years

SPECIFICATIONS

FEATURES

FOREST SHUTTLE MOTOR SPECIFICATIONS





SHUTTLE® iOn



14.8V DC Internal Lithium iOn battery + charger (3-4 months between charges) 30W

10 Nm 5.5" per second standard

< 40 dB(A) 55 lbs per motor 40 lbs per motor - curved track 2" x 3" x 12.25" CE/FCC/DOE White

V $\sqrt{}$ √ using RS485 & dry contacts 1 $\sqrt{}$ $\sqrt{}$ $\sqrt{}$ $\sqrt{}$ 10 Years on motor 2 years on battery pack

Our wide variety of control options make finding a fit for your windows easy - controlling the drapes by hand, remote or even by home automation system. Controlling the motorized system with your smart phone or tablet, you can create and schedule

customized room scenes that allow your drapes to operate on their own throughout the day no matter where you are.

Connector when integrating with Google Home, Apple Homekit, Amazon Alexa, Google



Assistant or Apple Siri

FOREST DIAMOND SENSE REMOTE

15-channel remote controls up to 15 motors individually and together, with a timer or manually. Range up to 98 feet. Wall mounted holder included.

With the Forest Wi-Fi Dongle, you can

smart phone or tablet using the Forest

control your motorized system with your

Connect app, or by voice command when integrated with Google Home, Amazon

FOREST WI-FI DONGLE

Echo and Siri.





FOREST WIRELESS CONNECTOR

With the Wireless Connector make your new or existing Shuttle motorized drapery system "smart". Add a smart plug and use with Apple Homekit, Google Assistant, or Amazon Alexa. Also, easily incorporate with building management systems, including dry contact controls.

BUILDING AUTOMATION / HOTEL ROOM CONTROLS

All 4 Forest Shuttles can be connected to any building automation system, by relay control.

SPECIFICATIONS

FEATURES

TOUCH CONTROL TECHNOLOGY INTEGRATED EMERGENCY CONTROL **RF COMMUNICATION STANDARD Z-WAVE COMMUNICATION** AUTOMATION SYSTEM COMPATIBLE WI-FI COMPATIBLE WORKS WITH DS-XL LED DIMMER WORKS WITH WIRELESS CONNECTOR CAN BE USED WITH CURVED TRACK PLUG & PLAY WARRANTY

MAX POWER TORQUE TRAVEL SPEED NOISE LEVEL MAXIMUM WEIGHT

VOLTAGE SHUTTLE

RECEIVER

BATTERY

DIMENSIONS CERTIFICATIONS/MARKINGS COLOR OPTIONS